

AMILO Display SL 3260W 26 Inch LCD widescreen

Issue August 2008

Pages 2

At a very attractive price, the AMILO Display SL 3260W offers superb multimedia and office performance. It will fit perfectly into your home environment and can replace your TV set also.

Highlights

- 26-inch widescreen display for a high definition video support up to 1080P with HDCP content protection
- Stylish black design with a piano black glossy front
- Frame rate conversion (fill to aspect ratio)
- Theme mode for optimized picture
- HDMI interface build in

Ergonomics


- Optimum flicker-free and distortion-free picture
- Excellent color purity
- Well balanced brightness uniformity
- Excellent Advanced Contrast Ratio (5,000:1)
- Space saving design

Technical highlights

- 26" (64.9 cm) LCD widescreen display
- Excellent contrast (ACR) 5,000:1
- Brightness 300 cd/m²
- Fast response time (typ.) 5 ms
- Internal power supply

Reliability

- Display Lifetime Extender
- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability



Visible screen diagonal	26 inch (64.9 cm)
Resolutions	
Pixels	1920 x 1200
Pixels*	1280 x 768
* expanded	
Picture size	550 x 344 mm
Colors	16.7 million
Pixel Pitch	0.2865 mm
Frequencies	
Horizontal	30 - 83 kHz
Vertical	56 - 75 Hz
Brightness (typical)	300 cd/m ²
Advanced Contrast Ratio	5,000:1
Viewing angle (CR > 10)	
Horizontal	170°
Vertical	160°
Response time (typical)	5 ms
Plug and Play	VESA DDC/CI
Setting options	
Menu language (16 languages)	
Power saving mode with Lifetime Extender	
Input signal select	
Theme Mode	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase, Color temperature and individual color setting	
Auto-adjust (direct access key)	
Factory recall setting	
OSD Language	
English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Finnish, Danish, Norwegian, Russian, Polish, Hungarian, Czech and Turkish	
Base	
Tilt angle	-5° / +15°
Video input	1x HDMI 1x DVI-D (HDCP support) 1x D-SUB
Audio input / output	
Audio signal input	3.5 mm stereo phone jack
Audio output (speaker)	2 W (L) + 2 W (R)
Audio output (headphone)	3.5 mm stereo phone jack

Electrical values (internal power supply)	
Rated voltage	100 - 230 V
Frequency	50 - 60 Hz
Power draw	
EPA 'on mode'	34 W
EPA 'Max.'	< 65 W
EPA 'off mode'	< 0.8 W
Protection class	1
Temperatures/ dimensions/ weight	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	475.5 x 603.7 x 238.7 mm
Weight (Monitor only)	8,5 kg
Reliability	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight (brightness > 50 % of original brightness)	30,000 h
Compliance with standards	
Product safety	EN60950
Ergonomics	ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 2004/108/EEC (EN55022/B, EN55024 EN61000-3-2/-3)
Ecology	RoHS, IT-Eco-declaration, Energy Star (EPA 4.1)
Accessories	
Power cable (1.8 m)*	1x wall socket (Euro-Schuko-Type CEE7)
Data cable (1.8 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5 mm stereo phone jack
* detachable on display	
Special features	Standardized mounting interface according VESA FPMPI (100 mm) Kensington Lock
Order code	S26361-K1285-V181
EAN	4333643810665
SAP product name:	AMILO LSL 3260W